



Barn Door: Brush Seal Installation

Typical Bill of Materials:



- 1) Top Brush Seal: 45deg Holder x Door Width x 1.5" – 3.0" Brush
- 2) Side Brush Seal: Straight Holder x Door Height x 1.5" – 3.0" Brush
- 3) Fasteners: Self-drilling fasteners included with brush seals

Tools Required:

- 1) Screw gun or drill for fasteners
- 2) Hack saw or sawzall for cutting Brush Seals and Holders



Step 1: Remove any existing weather stripping from the inside of the barn door.



Tops: 45deg Holder and Brush

Step 2: Mount the 8' Long 45deg Brush Seal across the interior top of the door header. Ensure the brush is making contact with the door panel across the entire length.

Step 3: Measure the remaining distance across the top and cut down the required length of brush seal.



Sides: Straight Holder and Brush

Step 4: Measure the distance from the finished floor to the top brush seal. Cut down the brush seal as required.

Step 5: The side seals will use the straight holder brush seal to ensure free horizontal movement in both directions.

Step 6: Mount the brush seal along the side of the barn door. Ensure a tight seal against the door.



Step 7: Open and Close the door to ensure a proper seal.



Thanks for your business!

Any question call 414.403.1625 or email

jason@jacorinc.com or corey@jacorinc.com

JaCor, Inc. • S83W18346 Saturn Drive • Muskego, WI 53150
jason@jacorinc.com • Phone: 414.403.1625 • Fax: 866.598.8987

www.jacorinc.com